

VISTA-15P CONTROL PANEL



The versatile Vista-15P is the ideal choice for any residential installation. Hardwired expansion, graphic keypad support, two-wire smoke, detectors, scheduling options and a host of end-user and installer features separate the VISTA-15P from all other six-zone panels – offering you and your customers the most panel for the dollar.

FEATURES

- Six on-board hardwired zones
 - 16 hardwired expansion zones totalling 22
 - 26 wireless expansion zones
 - Supports 6270 and 8132 graphic touchscreen keypads
 - Eight independent keyfob zones allow wireless keys to be programmed without using any of the 26 zones
 - Eight output devices
 - Relays (Model 4204 Relay Modules, or 4229 Expansion Module), and/or
 - X-10® devices (when used with a 1361X10 Transformer)
 - Two low current on-board trigger outputs
 - 50 Event Log viewable at system keypads with time/date stamp
 - 32 system user codes
 - Two installer configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes
 - Multiple actions on output devices depending on system "state"
 - Turns light off when system arms
 - Turns same lights on when system disarms
 - Flashes same lights when system is in alarm
 - Built-in phone line cut monitor with programmable delay and annunciation options
 - Display on system keypads
 - Trigger local sounders
 - Trigger system bell
 - Supports four-wire, and up to 16 two-wire smokes
 - Works with Sentrol CleanMe™ maintenance signal
- ### Valuable End-User Features
- Now viewable on system keypads:
 - Exit countdown
 - Time and date display*
 - Event log*
 - Auto keypad backlighting on entry
 - Keyswitch arming
 - Programmable macro buttons and single-button arming
 - A variety of wireless remote controls for single-button operation
 - User Scheduling
 - Automatically activates X-10 and relays at programmed times
 - Latchkey reports to pagers
 - Auto arm/disarm
 - "User access" time windows
- ### Security Dealer Features
- Supports up to two numeric pagers
 - VIP Module allows system control from any touchtone phone
 - Chime by zone
 - Automatic System Load Shed
 - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries
 - Dynamic Signaling
 - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet Radio
- *Requires custom alpha keypad

VISTA-15P

CONTROL PANEL

SPECIFICATIONS

Electrical

- Aux. power 12VDC, 600mA maximum
- Seven hour standby at 400mA aux. load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0 amps maximum
- For UL installations, combined aux. and alarm output cannot exceed 700mA

Output Control

- Supports a maximum of eight output devices (combination of relays and/or X-10) plus two onboard triggers

Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus two configurable zone types
- Programmable swinger suppression

Expansion Devices

- 4219 – Eight hardwired zones – 16mA
- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)
- 4229 – Eight hardwired zones and two relays – 36mA (each active relay draws an additional 40mA)

Accessories

- 4286 VIP Voice Module – 220mA
- 5881ENL supports up to eight zones – 60mA, 5881ENM supports up to 16 zones – 50mA, 5881ENH supports up to 26 zones – 50mA
- 5883 Transceiver supports up to 26 zones – 80mA
- Supports Eagle 1225 and 1221 boards

Keypads

- 6160 Custom Alpha (required for programming) – 100mA
- 6160V Custom Alpha Voice – 100mA
- 6150 Fixed English LCD - 85mA/40mA
- 6150V Fixed English Voice LCD – 85mA/40mA
- 6150RF Fixed English RF LCD - 85mA/40mA
- 6148 Fixed English LCD – 70mA/30mA
- 6270 Graphic touchscreen
- 8132 Advanced User Interface

Agency Listings

- UL Residential Fire, Burglary and CSFM

Smoke Detectors

- Supports up to 16 two-wire smoke detectors
- Supports four-wire smoke detectors

Communications

- Touchtone or pulse
- Formats supported
 - ADEMCO Contact ID
 - ADEMCO 4 + 2 Express
 - ADEMCO low speed
 - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
 - Split
 - Dual
 - Split/Dual – True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

ORDERING

VISTA-15P

VISTA15P Control Panel

Honeywell Security & Custom Electronics

Honeywell International Inc.
PO Box 9035
Syosset, NY 11791
www.honeywell.com

RE06041
L/VISTA15P/D
August 2006
© 2006 Honeywell International Inc.

Honeywell